

HG wallpaper remover

- super concentrated
- simply the best
- for max. 200 m²

Stripping wallpaper made easy! No more messy work with a steam machine and disintegrating wallpaper. HG wallpaper remover is a super-concentrated and extremely powerful substance capable of dissolving any type of wallpaper glue, which causes any sort of wall paper to simply fall off the wall. And it does it in complete strips at a time!

Directions for use:

Preliminary treatment: Washable, waterresistant, vinyl, metallic or emulsion painted wallpaper must first be opened up using course sandpaper. With wallpaper that can be stripped off you must first remove the top, outer layer. Ordinary paper and absorbent types of wallpaper do not require this preliminary treatment.

Dosage: Light weight wallpaper: 125 ml per 10 litres of water (1/4 of this bottle) Heavy wallpaper: 250 ml per 10 litres of water.

Heavy wallpaper: 250 ml per 10 litres of wat (1/2 of this bottle)

Removing the wallpaper:

- The easiest way to apply the solution is by using a pumppressure spray or a plant spray. You can also apply using a large brush or a sponge.
- 2. Moisten the wallpaper thoroughly.
- 3. Let it soak in for between 5 and 15 minutes.
- 4. If the wallpaper dries (becomes matt) after a few minutes, repeat step 2.



0530800105006 2305



- 5. Make a start by loosening a corner, using a scraper or a filling-knife if needed.
- Continue removing the thoroughly wet wallpaper using zig-zag motions. Try to remove the wallpaper in whole strips if possible. If this is difficult use a scraper or filling-knife.

Coverage: for the removal of $100-200 \text{ m}^2$ wallpaper.

Attention: Transport and store the bottle upright. Avoid contact with furniture and floors preferably by covering them.

Medical personnel can request the data sheet via +31 36 54 94 777

The consumer's information sheet can be obtained via www.HG.eu

contains a.o.:
non-ionic surfactants 5-15%

DANGER H318- Causes serious eye damage. P101- If medical advice is needed, have product container or label at hand. P102- Keep out of reach of children. P280- Wear eye protection. P305+P351+P338- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

lenses, if present and easy to do. Continue rinsing. Contains: Isotridecanol, ethoxylated EINECS: 500-241-6 Made in

Made in
The Netherlands by HG International b.v.,
P.J. Oudweg 41, 1314 CJ Almere.

The Netherlands, Tel.: +31 36 54 94 700

UFI: 8PHH-RV8P-H00G-281F

HG Does what it promises.

UK importer: HG UKI Ltd, Weston Business Centre, Parsonage Road, Takeley, Essex, CM22 6PU. Tel.: +44 (0) 1206 822 744