

### ***HG parquet & wood hard wood stain resistant floor oil 'natural'***

HG HG parquet & wood hard wood stain resistant floor oil 'natural' is a conditioning oil based on Chinese Tung oil and other natural, harvestable raw products, for unvarnished wooden flooring, parquet and untreated cork. HG HG parquet & wood hard wood stain resistant floor oil 'natural' impregnates, nourishes and protects against dirt and staining by water and other liquids. Gives wood a natural look and deepens the colour, while accentuating the wood structure. 100% solvent-free, and fully biodegradable.

#### **Directions:**

1. The surface must be unvarnished, clean and free of dust, grease, wax, oil and polish. Floors previously treated with a floor oil must be sanded beforehand. Cork floors must not be sanded.
2. Shake HG parquet & wood hard wood stain resistant floor oil 'natural' well before use.
3. Apply a thin layer of the oil with a lint-free cloth.
4. Saturate the surface (once or twice).
5. Remove excess oil within 1 minute and rub it out (A (glossy) layer must not be formed).
6. The floor can be walked on after 24 hours and used completely normally after 3 days.

**Use:** ± 20-50m<sup>2</sup> per litre, depending on how porous the wood is.

#### **Maintenance:**

- Wipe up spilt liquids as soon as possible (wine, coffee, water etc...).
- The floor can be cleaned using HG HG parquet & wood hard wood floor oil cleaner
- Remove stubborn stains and/or intensive soiling with HG parquet & wood hard wood floor oil powerful cleaner.
- HG HG parquet & wood hard wood stain resistant floor oil 'natural' can be used locally to touch up damage (worn out patches) and/or scratches.

**Caution:** • Not suitable for veneer parquet, laminate parquet, click parquet or other fully glued wooden floors that are not fully varnished, because the seams may swell up if they are not fully sealed. Use HG laminate products for those types of parquet. • The best results are achieved when drying (and using) at a temperature of 15-25°C and a relative humidity of 50-80%. Ventilation aids drying. Under less favourable conditions, a longer drying time will be required. If the floor has been sanded or a wax layer has been removed, first try the floor oil on an inconspicuous patch, in case of any residual varnish or wax. Test a small patch and wait 1 minute to check whether the oil penetrates the wood. If the oil does not penetrate the floor, we advise the following: Varnished floors: re-sand the floor and repeat the above procedure, if the oil still does not penetrate the floor, re-apply HG parquet & wood lacquer or opt for the HG wax system, namely HG parquet & wood anti vlek primer” and HG parquet & wood wax naturel, Waxed floors: Apply HG parquet & wood wax naturel for protection. We also advise applying the HG anti vlek primer beforehand as extra protection.

- Can be kept ± 1 year after opening, if stored in a closed packaging.
- **Absorbent materials, such as rags etc, that have come into contact with this product can overheat during drying which can lead to smouldering and even combustion. Spread the used materials properly and leave them to dry**

in the air. Alternatively you can soak the rags in water, place them in an airtight bag, and throw them away. We do not recommend the use of spongy materials, because of the possibility of catching fire due to overheating.

**Precautionary measures:**

- **S2** - Keep out of the reach of children.
  - **S20**- Do not eat or drink during application.
  - **S24/25** - Avoid contact with eyes and skin.
  - **S46**- If swallowed, seek medical advice immediately and show this container or label.
  - Wear suitable gloves..
  - Contains Cobalt Octoate. May produce an allergic reaction
  - Cloths used for heating purposes can be ignited by: expanded dry.
  - Do not expose to fire or heat
  - Do not eat or drink during application.
- 
- Medical personnel can request the data sheet via +31 (0)36-54 94 777
  - The consumer's information sheet can be obtained via [www.HG.eu](http://www.HG.eu)

QUESTIONS ABOUT CLEANING AND MAINTENANCE? [www.HG.eu](http://www.HG.eu)