


ve1612

HG **tough job**

silicon seal remover



- easily strips stubborn seals
- works within 15 minutes
- does not affect other materials
- with brush and spatula

100 ml e

HG silicon seal remover

Before proceeding to apply a new silicon joint, it is important to completely remove the remains of the previous joint in order to obtain a totally impermeable result. This is an unpleasant task which takes time. HG "silicon seal remover" will remove old seals quickly and easily. HG "silicon seal remover" has been specially developed to remove silicon seals from surfaces such as: stainless steel, enamel, various sorts of plastic, ceramic, sealed or non-porous natural stone and other similar materials. HG "silicon seal remover" has a pleasant odour, is easy to apply and will not damage the surfaces mentioned above. Traces of numerous other sorts of seals such as acrylic, butylene and universal seals can also be removed with HG "silicon seal remover".

Directions for use:
First remove as much of the old seal as possible, using a knife to cut it away from the edge of the surface to be treated. Any adjoining areas of seal should be protected with adhesive tape. Apply HG "silicon seal remover" liberally using the brush provided. Allow 15 minutes for HG "silicon seal remover" to work. Once the seal has loosened remove with the spatula provided. If there is some resistance, leave the product to work for a few minutes more. Finally remove the last traces of HG "silicon seal remover" by rinsing with clear water using a cloth or nail brush if necessary to remove any last traces. Repeat the treatment if necessary. Allow the surface to dry completely before re-applying a seal.

Coverage:
100 ml will treat at least 10 to 15 metres.

Attention: Transport and store the box upright. We recommend to test HG "silicon seal remover" in a small and inconspicuous place first. Do not use on porous materials. Before treating a new silicon seal, make sure that the surface is completely dry.


Medical personnel can request the data sheet via +31 (0)36 54 94 777
The consumer's information sheet can be obtained via www.HG.eu

QUESTIONS ABOUT CLEANING AND MAINTENANCE? www.HG.eu

UK importer:
HG Hagesan (UK) Ltd,
Weston Business Centre,
Parsonage Road, Takeley,
Essex, CM22 6PU.
Tel.: +44 (0) 1206 822 744 0629000101006 2012

HG **tough job**

silicon seal remover



- easily strips stubborn seals
- works within 15 minutes
- does not affect other materials
- with brush and spatula

100 ml e

Other HG products

HG wallpaper remover

Stripping wallpaper made easy! No more messy work with a steam machine and disintegrating wallpaper. HG "wallpaper remover" is a super-concentrated and extremely powerful substance capable of dissolving any type of wallpaper glue, which causes any sort of wall paper to simply fall off the wall. And it does it in complete strips at a time!



HG sticker remover

removes stickers, sticker glue, sellotape, tar, oil, scuff marks and many other problems from most surfaces.



WARNING H226- Flammable liquid and vapour. **H315-** Causes skin irritation. **H317-** May cause an allergic skin reaction. **H319-** Causes serious eye irritation. **H410-** Very toxic to aquatic life with long lasting effects. **P101-** If medical advice is needed, have product container or label at hand. **P102-** Keep out of reach of children. **P280-** Wear protective gloves. **P305+P351+P338-** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. **P333+P313-** If skin irritation or rash occurs: Get medical advice/attention. **P501-** Dispose of contents and container in accordance with all local, regional, national and international regulations. Contains: dipentene EINECS: 227-813-5.

Made in The Netherlands by HG International b.v., Damsluisweg 70, 1332 EJ Almere, The Netherlands, Tel.: +31 (0)36-5494700

